

GO GO

ELITE TRAVELLER®

3 & 4-WHEEL SCOOTER

THE QUICKEST WAY TO TRAVEL



Feather-touch disassembly

The compact design of the **Go-Go Elite Traveller®** allows you to easily maneuver in tight spaces while providing stable outdoor performance. With a 300 lb. weight capacity, charger port in tiller, one-hand feather-touch disassembly and maximum speeds up to 4 mph make it easy to go where you want to go with the Go-Go Elite Traveller.



Go-Go Elite Traveller®
3-wheel shown with
optional under seat storage



Go-Go Elite Traveller®
4-wheel

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

SPECIFICATIONS

GO-GO ELITE TRAVELLER®

3W: SC40E 4W: SC44E

Weight capacity:	300 lbs.
Maximum speed ¹ :	Up to 4 mph
Ground clearance ² :	2"
Turning radius:	3W: 33" 4W: 44"
Overall length ² :	3W: 37" 4W: 39.5"
Overall width ² :	19.5"
Front tires:	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear tires:	2.5" x 8" solid
Range per charge ^{1,4} :	3W: Up to 7.2 miles (12 AH) 4W: Up to 6 miles (12 AH) 3W: Up to 10.4 miles (18 AH) 4W: Up to 9.7 miles (18 AH)
Total weight w/out batteries ⁵ :	3W: 76 lbs. 4W: 80 lbs.
Heaviest piece when disassembled:	3W: 29.5 lbs. (front section) 4W: 34 lbs. (front section)
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17", Depth: 17"
Motor output:	24-volt DC motor, sealed mini-transaxle
Brakes:	Regenerative and electromechanical
Battery requirements ^{3,5} :	(2) 12V Deep-cycle Size: (2) 12 AH, 9 lbs. each or (2) 18 AH, 14 lbs. each (optional) Weight: 12 AH: 20 lbs. per battery pack, 18 AH: 29.5 lbs. per battery pack
Battery charger:	Off-board, 2 amp
Color:	2 sets of exciting colors with every scooter!



Red



Blue

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards.

Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

FEATURES

- Feather-touch disassembly permits simple frame separation with only one hand
- Pride's exclusive black, non-scuffing tires
- Auto-connecting front to rear cable
- Includes sets of easily changeable colored panels - Red and Blue
- Front frame-mounted seat post offers maximum stability
- Frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Standard front tiller-mounted basket
- Removable footboard basket for additional storage (4-wheel version only)
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board
- Charger port in tiller
- Optional under seat storage (assembly required)

Pride Lifts & Ramps

Compatible Lifts:

- Backpacker® Plus
- Outlander Full Platform
- Backpacker® AVP
- Outlander TM
- Olympian